

Technical Data Sheet



:
: 02)894-8068 :: 02)894-8065

PRODUCT DESCRIPTION:	Contact Grease A35B	DATE:	03/97
PRODUCT CODE:	A35B	PAGES:	1

Electrolube

1950

Electrolube 가

A35B

A35B

Electrolube 가

Electrolube A35B

-40C

+125C

가

가

가

A35B

* -40

*

Pour Point (Base Oil)

- 50C

:

1.0

(%)

<0.15

(worked 20C)

295-350(Typical 320)

(IP50, 60 strokes)

/ (%)

2.2 1/4 cone

(IP183-63, 72hrs @ 100C)

Consistency:

Non-melting

Drop Point © ASTM D566:

250

(C):

200

Copper Strip Corrosion (IP154/69):

1

©

-40 - +125

1 Kg Bulk

A35B01K

Copyright Electrolube 1997

ELECTROLUBE Wentworth House, Blakes Road, Wargrave, Berkshire, RG10 8AW, UK

Telephone: +44(0) 118 940 4031/ 3014 Fax: +44(0) 118 940 3084

ISO 9002 Registered Firm. Certificate No. FM 32082

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.