Technical Data Sheet

제품문의: 정원케미칼
전화: 02)894-8068 팩스:: 02)894-8065

PRODUCT DESCRIPTION:	**Contact Grease CG53A**	**DATE:**	**03/97**
PRODUCT CODE:	**CG53A**	**PAGES:**	**1**

제품 개요

접촉 윤활유의 CG 시리즈는 매우 탁월하고 인기 있는 2X 시리즈의 연속물이다. 이 제품의 주요 특징은 접촉 저항성을 줄여주고(특히 매우 어려운 취급에 있어서도), 플라스틱의 적합성을 향상시키며 기계적 윤활 작용을 증진시키는 것이다. 스위치와 커넥터에 CG53A의 사용은 자동차 제조 산업에서 요구되는 오랜 수명에 대해 매우 낮고 안정적인 접촉 저항성을 보증한다.

예외적으로 낮은 마모 특징은 이 윤활유를 고품질 오디오와 자동차 제조 응용에 이상적으로 만들며, 매우 부드럽고 고품질의 감지 기능을 제공한다. 이 그리스의 플라스틱의 적합성은 항상 총규모 보호에 앞선 실험에 바람직함에도 불구하고 매우 훌륭하다.

성 질

색 깔 :		크림의 흰색
Drop Point (ISO 2176) :	200°C	
1/4 Cone Penetration (ASTM 217):	20°C	65 to 75
	-40°C	50 to 60 (Typical)
Worked Penetration(ASTM 217) :	20°C	295-340 (Typical 320)
Consisitency (DIN 51818)		NLGI 1-2
Fließdruck (DIN 51805) :	-40°C	<350 mBar
Oil Separation (DIN 51817/IP121) :		<8%
동 부식 (DIN 51759/IP112) :		Class 1a (4h @ 150°C)
은 부식 (DIN 51759) :		색깔 변화 없음 (3h @ 100°C)
Infra Red (DIN 51820) :		표준에 따름
주제 액체 :		항산화, 항부식과 금속 보호 첨가물을 포함한 합성 액체의 복합물질
Pour Point :		-41°C
비 중 (base oil @ 20°C) :		0.995 g/ml (ASTM D1298)
씨크너 :		복합의 유기질/무기질 씨크너
온도 범위 :		-40°C 에서 +130°C

포 장 / 주문 코드

포 장	주문 코드
35 mm Syringe	CG53A35SL
1 Kg Bulk (5 litres)	CG53A01K
5 Kg Bulk	CG53A05K
12.5 Kg Bulk	CG53A12.5K
25 Kg Bulk	CG53A25K

12.5Kg과 25 kg 그리스 통은 자동 제조 라인의 디스펜싱 기계와 함께 사용된다. 드럼 통 칫수는 :

12.5 kg 254mm (내부 직경) x 330mm (높이)
25 kg 305mm (내부 직경) x 406mm (높이)

Copyright Electrolube 1997
All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.