Technical Data Sheet

제품문의: 정원케미칼
전화: 02)894-8068 팩스:: 02)894-8065

PRODUCT DESCRIPTION:	**Peelable Coating Mask**	**DATE:**	**03/97**
PRODUCT CODE:	**PCM**	**PAGES:**	**1**

제품 개요

Peelable Solder Coating Mask 는 콘포멀 코팅 과정 중에 코팅이 되지 않게 하여야 할 콤포넌트, 코넥터와 다른 아이템을 마스킹하기 위한 유연한 솔벤트 저항의 라텍스입니다. 이것은 또한 웨이브 납땜 시 스폿 마스킹으로도 사용됩니다.
ELECTROLUBE Peelable Solder Coating Mask 은 고율의 고체, 자연 라텍스이며, 임시의 보호 물질입니다. 모든 Flux와 세척 약품으로부터 보호가 가능합니다.
Conformal Coating과 Wave Soldering의 적용 모두에 이상적인 뛰어난 제품이며, 복원율은 온도가 높아짐에 따라 빨라질 수 있습니다.

특 징

* 상온 또는 가열에 의한 빠른 건조
* 완전히 손으로 벗길 수 있고 잔해물을 남기지 않음
* 솔벤트에 의해 용해되지 않고 콘포멀 코팅을 포함치 않음
* 높은 필름 강도를 갖아 벗겨낼 때 끊어지지 않음
* 담금, 스프레이 또는 브러쉬로 적용된 콘포멀 코팅에 사용하기 적합함
* 탁월한 장력 (tensile strength) 및 훌륭한 점착성
* 고온 저항성과 빠른 건조 시간
* 결합물 점착성이 낮으며 높은 고체 성분
* 엷은 암모니아 냄새

대표적 성질

외관	점성 있는 엷은 초록색 계열
고체 성분	대략 60%
복원 시간	1 시간 이내
건조 시간	40 mins @ 22 ° C
대략의 점도	35.000 45.000 cps
최대 온도	266 ° C
특별 중력	1,091 kg/l
점도 조정	증류수로 조정 가능

건강과 안전

위에 내용에 대한 물질 안전 서류를 제공할 수 있습니다.

보 관

ELECTROLUBE PCM250은 주변 온도에서 원래의 포장용기에 보관되어 있을 경우 보존 기간이 12개월입니다. (최소 5 ° C ~ 최대 32 ° C)

PACKAGING	ORDER CODE
250ml Bottle	PCM250ML

Copyright Electrolube 1997
All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.