

SGB / SOB

-2-

	SOB	SGB
Kinematic (20°C) :	640 cSt	N/A
(ASTM D2270/74) :	220	N/A
(20°C) :	1.002	1.113
(°C) :	-37	N/A
(°C) :	-40 to +130	-35 to +130
(°C) :	210	N/A
(mm Hg) @ 20°C :	0.001	N/A
%		
(IP183-63 72 hours @ 100°C) :	0.9	2.34
(IP.112/56 @ 150°C) :	1	1
@ 20°C		
(ASTM D217 worked 60 Strokes) :	N/A	295-350 (320)
, (%) :	0.20	0.60
Drop :	N/A	250°C
Ash Percent (ASTM D-482, IP-4) :	0.01	N/A
Refractive Index :	1.45	N/A
Breakdown (kV @ 20°C) :	60.0	N/A

2X Oil

5 ml	SOB05P
55 ml	SOB55B
1 Kg	SOB01K
5 Kg	SOB05K
25 Kg	SOB25K
200 ml (100% , -가)	SOB200D

2X Grease

20 ml	SGB20S
35 ml	SGB35SL
200 ml (100% , 가)	SGB200D
1 Kg	SGB01K
5 Kg	SGB05K
12.5 Kg	SGB12.5K
25 Kg	SGB25K

2X Contact Cleaner Lubricant

200 ml (100% , 가)	EML200F
--------------------	---------

The 12.5 and 25 kg grease drums have parallel sides for use with "follower plate" dispensing equipment for automated manufacturing lines. The drum dimensions are:

12.5 kg 254mm () x 330mm ()
25 kg 305mm () x 406mm ()

Copyright Electrolube 1997

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.